

## FEATURES

- **Thin, flexible sticker format**
- **Low-cost, easily installed**
- **Ideal for electronic tolling, electronic vehicle registration, mCommerce, parking, and security access**
- **Non-battery**
- **Extended read range**
- **1024 bit read/write memory**

# eGo<sup>®</sup> Windshield Sticker Tag



**eGo Windshield Sticker Tag (shown actual size)**

The eGo<sup>®</sup> Windshield Sticker Tag is a 915 MHz radio frequency (RF)-programmable, beam-powered transponder. Packaged as a flexible sticker, this tag is ideal for applications that require low-cost, easily installed tags. The tag is suitable for a wide variety of automatic vehicle identification (AVI) transportation applications, including electronic tolling, electronic vehicle registration, *mCommerce*, parking, and security access applications.

TransCore's eGo Windshield Sticker Tag offers a new price/performance paradigm in radio frequency identification (RFID) technology. Using a revolutionary RFID tag-on-a-chip ASIC, the eGo Windshield Sticker Tag offers an extended read range of up to 31.5 feet (9.6 meters) and 1024-bit read/write memory at a fraction of the cost of older, less flexible RFID technology. The tag provides the capability to read, write, rewrite, or permanently lock individual bytes.

The eGo Windshield Sticker Tag is read by TransCore's eGo family of readers configurable to support a protocol compliant with the ANSI INCITS 256-2001 and the International Organization for Standardization (ISO) 18000-6 standards.

Optional features include custom external laser etching and custom programming. A tamper-resistant eGo tag and OEM tag inserts are also available.

# eGo® Windshield Sticker Tag

## COMMUNICATIONS

### Frequency Range

902 to 928 MHz

### Maximum Read Range

11.5 ft (3.5 m) with unlicensed readers, Federal Communications Commission (FCC) Part 15

31.5 ft (9.6 m) with licensed readers, FCC Part 90

### Read/Write Range

The write range is approximately 70% of the effective read range.

User-specified groups within a population of tags can be selected, read from, and/or written to using multi-tag access commands.

### Polarization

Linear, horizontal

### Anti-collision Protocol

Efficient, binary tree-type anti-collision algorithm

## SOFTWARE FEATURES

### Memory

EEPROM

Byte resolution memory addressing

Byte resolution memory lock

1024 bits total memory:

- Unique 64-bit tag ID locked at the factory
- 880 bits user memory formatted and locked as required by application. User memory includes 128 bits that are factory programmable.

### Data Rate

Read 8 bytes of data from a tag in less than 10 ms

Write a single byte of data to a tag in less than 25 ms

## LIFE EXPECTANCY

### Service Life

Capable of unlimited reads and more than 100,000 write transactions

## PHYSICAL

### Dimensions

1.81 x 3.11 x 0.05 in (46 x 79 x 1 mm)

### Mounting Surface

Attached by a semi-permanent adhesive to interior of a nonmetallic windshield 0.190 to 0.230 in (4.82 to 5.84 mm) in thickness

## ENVIRONMENTAL

### Operating Temperature

-40°F to +185°F (-40°C to +85°C)

### Storage Temperature

-58°F to +203°F (-50°C to +95°C)

### Humidity

95% condensing

### Vibration Tolerance

1.5 G<sub>rms</sub>, 5 to 1000 Hz, 3 axes

### Shock Tolerance

5 G, 1/2 sine pulse, 10 ms duration, 3 axes

### Chemical Exposure

No tag damage in the following situations:

- exposed to water washing of the backside of the sticker
- exposed to commonly spilled beverages, mild cleaning solutions, or vinyl plasticizers

## STANDARDS

Fully compliant with ANSI INCITS 256-2001 and ISO 18000-6

## OPTIONS

- Custom laser etching
- Customer-specific tag programming

## MODELS AVAILABLE

13-0510-003: Full-frame tag insert

13-0510-004: Full-frame sticker



**For product information call:** 1.800.923.4824 or 972.733.6600 (outside the U.S.) Fax 972.733.6486

[www.transcore.com](http://www.transcore.com)

© 2004 TC IP, Ltd. All rights reserved. TRANSCORE and EGO are registered trademarks of TC IP, Ltd., and are used under license. All other trademarks listed are the property of their respective owners. Contents subject to change. Printed in the U.S.A. Products covered by this document are protected by one or more of the following U.S. patents 5,030,807; 5,528,222; 5,550,547; 5,606,323; 5,673,037; 5,889,489; 5,912,632; 5,942,987; 6,097,347; 6,121,880; 6,275,157; and foreign equivalent patents. Other patents pending.